TrilliumSeries Adiabatic Condenser - Mee

Adiabatic cooling











Key benefits

- High thermal performance
- Saving water
- Top hygiene control

TVC, TrilliumSeries characteristics

Counter flow, adiabatic pre-cooling, axial fan, induced draft

Capacity range

340 - 1030 kW

Typical applications

- Small to medium industrial refrigeration applications
- · Locations with limited water and space availability



Boosting high thermal performance

- Pads in front of the finned coil pre-cool air to virtual wet bulb temperature.
- Up to 40% improved capacity compared to dry cooling.
- TVC condenser consumes less energy.
- TVC condenser achieves low process temperatures.

Saving water

• TrilliumSeries condensers **achieve annual water savings exceeding 80%** water compared to normal water cooled condensers by limited adiabatic operation.

Top hygiene control

- Featuring a **once-through system**: recirculation and stagnation of water eliminated.
- No stagnant water: pre-cooler water conveyed from pads to sewer via a gutter.
- No aerosol formation: TrilliumSeries condensers minimize the Legionella risk.
- TrilliumSeries condensers cool incoming air without transferring water to the dry coil

Interested in the TVC TrilliumSeries condenser for your refrigeration project? Contact your local <u>BAC</u> representative for more information.

Downloads

- TVC Refrigerant condensers
- Spare Parts for TrilliumSeries adiabatic cooler Model TVC
- Maintenance TVC
- Rigging TVC
- Why should you buy BAC adiabatic products?