



CXVE 1012-1018

Previous generation products

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

Last update: 01/01/2025

CXVE 1012-1018



1. Refrigerant in; 2. Refrigerant out; 3. Make up; 4. Overflow; 5. Drain; 6. Access door.



Model	Weights (kg)			Dimensions (mm)			Air Flow (m³/s)	Fan Motor (kW)	Water Flow (l/s)	Pump Motor (kW)	R717 charge (kg)
	Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H					
CXVE 244-10 12-15L	8030	5130	2950	3651	2997	5199	33.2	(2x) 5.5	54.6	(1x) 5.5	72.0
CXVE 256-10 12-20L	8060	5160	2980	3651	2997	5199	36.2	(2x) 7.5	54.6	(1x) 5.5	72.0
CXVE 273-10 12-15L	8820	5880	3700	3651	2997	5199	32.5	(2x) 5.5	54.6	(1x) 5.5	119.0
CXVE 274-10 12-30L	8110	5210	3030	3651	2997	5199	39.9	(2x) 11.0	54.6	(1x) 5.5	72.0
CXVE 289-10 12-20L	8850	5900	3730	3651	2997	5199	35.5	(2x) 7.5	54.6	(1x) 5.5	119.0
CXVE 308-10 12-30L	8900	5950	3770	3651	2997	5199	39.1	(2x) 11.0	54.6	(1x) 5.5	119.0
CXVE 301-10 12-15L	9460	6490	4520	3651	2997	6080	32.3	(2x) 5.5	54.6	(1x) 5.5	143.0
CXVE 311-10 12-15L	9580	6610	4650	3651	2997	6080	32.3	(2x) 5.5	54.6	(1x) 5.5	143.0
CXVE 313-10 12-15L	10250	7230	5270	3651	2997	6080	32.0	(2x) 5.5	54.6	(1x) 5.5	191.0
CXVE 326-10 12-20L	9880	6890	4920	3651	2997	6080	35.0	(2x) 7.5	54.6	(1x) 5.5	167.0
CXVE 327-10 12-15L	10760	7720	5760	3651	2997	6080	31.8	(2x) 5.5	54.6	(1x) 5.5	215.0
CXVE 328-10 12-20L	9610	6640	4680	3651	2997	6080	35.2	(2x) 7.5	54.6	(1x) 5.5	143.0
CXVE 332-10 12-20L	10270	7260	5300	3651	2997	6080	34.8	(2x) 7.5	54.6	(1x) 5.5	191.0
CXVE 340-10 12-20L	10240	7230	5270	3651	2997	6080	34.9	(2x) 7.5	54.6	(1x) 5.5	179.0
CXVE 341-10 12-30L	9530	6560	4600	3651	2997	6080	38.8	(2x) 11.0	54.6	(1x) 5.5	143.0
CXVE 347-10 12-20L	10790	7750	5790	3651	2997	6080	34.7	(2x) 7.5	54.6	(1x) 5.5	215.0
CXVE 353-10 12-30L	9930	6940	4970	3651	2997	6080	38.6	(2x) 11.0	54.6	(1x) 5.5	167.0
CXVE 355-10 12-30L	9660	6690	4730	3651	2997	6080	38.8	(2x) 11.0	54.6	(1x) 5.5	143.0
CXVE	10320	7310	5350	3651	2997	6080	38.5	(2x)	54.6	(1x)	191.0



359-10 12-30L								11.0		5.5	
CXVE 365-10 12-30L	10710	7670	5700	3651	2997	6080	38.3	(2x) 11.0	54.6	(1x) 5.5	215.0
CXVE 376-10 12-30L	10820	7780	5820	3651	2997	6080	38.3	(2x) 11.0	54.6	(1x) 5.5	215.0
CXVE 388-10 18-30L	11920	7520	4240	5480	2997	5349	54.5	(3x) 7.5	85.2	(1x) 7.5	107.0
CXVE 396-10 18-22.5 L	12480	8040	4760	5480	2997	5349	49.5	(3x) 5.5	85.2	(1x) 7.5	143.0
CXVE 414-10 18-45L	12030	7630	4350	5480	2997	5349	60.1	(3x) 11.0	85.2	(1x) 7.5	107.0
CXVE 419-10 18-22.5 L	13070	8600	5320	5480	2997	5349	49.1	(3x) 5.5	85.2	(1x) 7.5	179.0
CXVE 419-10 18-30L	12510	8080	4800	5480	2997	5349	53.9	(3x) 7.5	85.2	(1x) 7.5	143.0
CXVE 439-10 18-30L	13100	8640	5350	5480	2997	5349	53.5	(3x) 7.5	85.2	(1x) 7.5	179.0
CXVE 446-10 18-45L	12620	8190	4910	5480	2997	5349	59.5	(3x) 11.0	85.2	(1x) 7.5	143.0
CXVE 469-10 18-45L	13220	8750	5470	5480	2997	5349	59.1	(3x) 11.0	85.2	(1x) 7.5	179.0
CXVE 461-10 18-22.5 L	14060	9560	6590	5480	2997	6230	48.8	(3x) 5.5	85.2	(1x) 7.5	215.0
CXVE 483-10 18-30L	14090	9590	6620	5480	2997	6230	53.2	(3x) 7.5	85.2	(1x) 7.5	215.0
CXVE 491-10 18-22.5 L	15110	10550	7590	5480	2997	6230	48.3	(3x) 5.5	85.2	(1x) 7.5	268.0
CXVE 502-10 18-22.5 L	15960	11350	8380	5480	2997	6230	47.9	(3x) 5.5	85.2	(1x) 7.5	322.0
CXVE 502-10 18-30L	14220	9710	6750	5480	2997	6230	53.2	(3x) 7.5	85.2	(1x) 7.5	215.0
CXVE 519-10 18-45L	14210	9700	6740	5480	2997	6230	58.7	(3x) 11.0	85.2	(1x) 7.5	215.0
CXVE 521-10 18-30L	15140	10590	7620	5480	2997	6230	52.7	(3x) 7.5	85.2	(1x) 7.5	268.0
CXVE 533-10 18-30L	15990	11380	8410	5480	2997	6230	52.2	(3x) 7.5	85.2	(1x) 7.5	322.0



CXVE 539-10 18-45L	14330	9830	6860	5480	2997	6230	58.7	(3x) 11.0	85.2	(1x) 7.5	215.0
CXVE 563-10 18-45L	15260	10700	7730	5480	2997	6230	58.1	(3x) 11.0	85.2	(1x) 7.5	268.0
CXVE 575-10 18-45L	16080	11470	8510	5480	2997	6230	57.6	(3x) 11.0	85.2	(1x) 7.5	322.0